

## 64-06 Metal Industrial Barcode Printer, 300 dpi, cutter, print width 164 mm, repas

Novexx 64-06 is high volume industrial label printer for printing at high speed to increase performance within any industry. It is the ideal solution to meet the demanding requirements of industrial applications in logistics and transportation centers, industry and retail.

Great standard features such as the Ribbon Save Function, 600 meter film rolls, print width up to 203 mm (8 in.) and print speed up to 400 mm/s offer immediate cost savings without compromising print quality.



The Ribbon Save mechanism automatically stops the feed of thermal transfer ribbon at every point where the label is not to be printed. The print head is only lowered and heated when printing is required. Large ribbon feed capacity of up to 600 m means fewer stops to change supplies, enhancing productivity.

### Key features:

- Ribbon Save Function
- Print speed up to 356 mm/s
- Robust and reliable print performance - 400 MHz processor
- Printhead is quickly and easily exchangeable



# Technical Description

## Functionality & Operation

|                          |  |
|--------------------------|--|
| Expansion slot           | SD/MMC slot  |
| Print resolution         | 300dpi   |
| Print mode               | thermal-transfer, direct thermal   |
| Communication interface  | USB Host, USB, Ethernet, RS232   |
| Fonts & barcode rotation | 0°, 90°, 180°, 270°  |
| Memory                   | 4MB Flash, 64 MB SDRAM   |
| Maximal print width      | 164mm  |
| Print speed              | 356mm/sec  |
| Display type             | 2-line, 16-character graphic   |
| 1D Barcode Symbolologies | All standard one-dimension barcodes  |
| 2D Code Symbolologies    | QR code, PDF417, Data Matrix, MaxiCode, Codablock F, GS1 DataBar Composite Code, Code 49 |

## Optical

|         |                          |
|---------|--------------------------|
| Sensors | reflective, transmissive |
|---------|--------------------------|

## Mechanical

|            |   |
|------------|---|
| Dimensions | Width: 350mm, Height: 305mm Length: 490mm |
| Weight     | 21.5kg                                    |

## Consumables

|                       |   |
|-----------------------|---|
| Media core diameter   | 38 to 102mm   |
| Max. ribbon length    | 600m  |
| Ribbon width          | 30 to 164mm   |
| Media thickness       | to 240g/m2  |
| Media type            | continuous, fan-fold, tags, paper and thermal-paper labels, black-marked media, notch, perforated |
| Maximal paper width   | 185mm   |
| Maximal roll diameter | 210mm   |
| Minimal paper width   | 30mm  |

## Environment

|                       |             |
|-----------------------|-------------|
| Operating temperature | 5 to 35°C   |
| Storage temperature   | -20 to 70°C |

**CODEWARE, s.r.o.**  
Jaromírova 484/37  
120 00 Praha 2 - Nusle  
IČ: 61061395, DIČ: CZ61061395

+420 222 562 444  
codeware@codeware.cz  
<https://www.codeware.cz/>

